

**Government of India**  
**Ministry of Health & Family Welfare**  
**National Institute of Public Health Training & Research,**  
**332, S.V.P. Road, Khetwadi Mumbai.**

Tender enquiry no: NIPHTR/Curtains/ 2019-20/

Date - 30/01/2020

**RE-TENDER NOTICE**

National Institute of Public Health Training & Research (NIPHTR), Mumbai is inviting sealed tender in the prescribed format from the reputed agencies for supply and installation of **“Roller Blinds and Curtains”** at New Institutional & Hostel building of NIPHTR at Plot no.6 & 6 A, Sector 18, New Panvel, Navi Mumbai as per Annexure-1.

Interested agencies can access the tender document, terms & conditions of the tender from the website of NIPHTR, [www.fwtrc.gov.in](http://www.fwtrc.gov.in) or collect personally from Administration section, NIPHTR, Mumbai. The cost of tender document is Rs 500/-.

**The last date of submission of tender is up to 07/02/2020 up to 5.00 PM.**

The Director, NIPHTR, Mumbai reserves the right to reject any or all tender without assigning any reason whatsoever.

**Terms & Conditions**

1. The tender fees of Rs. 500/- (Non Refundable) should be submitted with the tender in the form of DD/Pay-order in favour of Director, NIPHTR, Mumbai, payable at Mumbai.
2. The bidder has to submit EMD (Refundable) of Rs.25, 000/-(Rupees Twenty Five Thousand only) with the tender in the form of DD/Pay-order in favour of Director, NIPHTR, Mumbai, payable at Mumbai.
3. The Bidder should inspect the site before filling in and submitting the tender for understanding the scope of work.
4. The tender is non-transferable, subletting will not be allowed
5. Rates shall be quoted including all govt. taxes, transportation, freight charges, installation and packing charges etc.
6. Tenders in the prescribed format as per Annexure – I shall only be considered. Offers not received in the prescribed format shall be rejected without any correspondence.
7. Tenders received after due date shall not be accepted.
8. Tenders sent by e-mail and fax shall not be considered.
9. Contract shall be awarded to the firm offering lowest net bundled price and not with the reference to the lowest prices quoted for the sub items.
10. The agency should complete the entire work as per the contract within 10 days from award of the contract.

**Sd/-**  
**DIRECTOR,**  
**NIPHTR, 332 S.V.P. ROAD, KHETWADI,**  
**MUMBAI-04**  
**Phone -022-23881724 / 23893165**

**Annexure-I**

ITEMS	Quantity	Rate	Total
<p>1. Classic Roller – Blind Sunscreen Make: Vista- 5% Shade: 573 ROLLER TUBE: Made of anodized aluminium 38 mm Dia. Of high strength alloy With wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM: Moulded plastic having antifriction additive with Glass fibre reinforcement. Should have a minimum lifting capacity of 8 lbs OPERATING CHAIN: made of 4.5mm plastic beads molded on 2.2mm thick polyester chord. The pitch of the bead is 6mm. Chain adoptable to the clutch pitch for smooth lifting &amp; lowering of blind. LOCKING MEMBER: stop locks for limit setting adoptable to the chain. LOAD TUBE : 38 mm Extruded aluminium wall thickness :1.2 mm + / - 5% Bonding ( Fabric &gt; Tube ) : 15 mm wide double sided adhesive tape Bottom Bar: aluminium extruded rail with a groove for fixing the fabric and powder coated in white. The fabric is fitted to the tube using plastic insert for perfect fall of fabric to avoid warpage / floating. Installation to be insert type with end caps. Vista Screen Classic series to be with 5% Openness Composition : 25 % Polyester, 75 % PVC Thickness : 0.65 MM Openness Factor : 3% Weight : 465 GSM Fire resistance of the fabric : NFPA 701, BS 5867 Part-2-TYPE-A Colour Fastness - Grade 8 warranty - 1 year</p>	800 Sq. Ft.		
<p>2. Classic Roller – Blind Sunscreen Make: Vista- 5% Shade: 553 ROLLER TUBE: Made of anodized aluminium 38 mm Dia. Of high strength alloy With wall thickness</p>	3655.72 Sq. Ft.		

<p>of 1.2 mm with spline adoptable to accommodate clutch.</p> <p><b>CLUTCH MECHANISM:</b> Moulded plastic having antifriction additive with Glass fibre reinforcement. Should have a minimum lifting capacity of 8 lbs</p> <p><b>OPERATING CHAIN:</b> made of 4.5mm plastic beads molded on 2.2mm thick polyester chord. The pitch of the bead is 6mm. Chain adoptable to the clutch pitch for smooth lifting &amp; lowering of blind.</p> <p><b>LOCKING MEMBER:</b> stop locks for limit setting adoptable to the chain.</p> <p><b>LOAD TUBE :</b> 38 mm Extruded aluminium wall thickness :1.2 mm + / - 5%</p> <p><b>Bonding ( Fabric &gt; Tube ) :</b> 15 mm wide double sided adhesive tape</p> <p><b>Bottom Bar:</b> aluminium extruded rail with a groove for fixing the fabric and powder coated in white. The fabric is fitted to the tube using plastic insert for perfect fall of fabric to avoid warpage / floating. Installation to be insert type with end caps.</p> <p><b>Vista Screen Classic series</b> to be with 5% Openness</p> <p><b>Composition :</b> 25 % Polyester, 75 % PVC</p> <p><b>Thickness :</b> 0.65 MM</p> <p><b>Openness Factor :</b> 3%</p> <p><b>Weight :</b> 465 GSM</p> <p><b>Fire resistance of the fabric :</b> NFPA 701, BS 5867</p> <p><b>Part-2-TYPE-A</b></p> <p><b>Colour Fastness - Grade 8</b></p> <p><b>warranty - 1 year2</b></p>			
<p>3. Classic Roller – Blind Blackout</p> <p><b>Make - Vista</b></p> <p><b>Shade - Serene Opaque Sand &amp; Grey</b></p> <p><b>ROLLER TUBE:</b> Made of anodized aluminium 38 mm Dia. Of high strength alloy With wall thickness of 1.2 mm with spline adoptable to accommodate clutch.</p> <p><b>CLUTCH MECHANISM:</b> Moulded plastic having antifriction additive with Glass fibre reinforcement. Should have a minimum lifting capacity of 8 lbs</p> <p><b>OPERATING CHAIN:</b> made of 4.5mm plastic beads molded on 2.2mm thick polyester chord. The pitch of the bead is 6mm. chain adoptable to the clutch pitch for smooth lifting &amp; lowering of blind.</p> <p><b>LOCKING MEMBER:</b> stop locks for limit setting adoptable to the chain.</p>	602.6 Sq. Ft.		

<p>LOAD TUBE : 38 mm Extruded aluminium wall thickness :1.2 mm + / - 5%</p> <p>Bonding ( Fabric &gt; Tube ) : 15 mm wide double sided adhesive tape</p> <p>Bottom Bar: aluminium extruded rail with a groove for fixing the fabric and powder coated in white. The fabric is fitted to the tube using plastic insert for perfect fall of fabric to avoid warpage / floating. Installation to be insert type with end caps.</p> <p>Vista Serene Opaque series to be with 0% Openness</p> <p>Composition : 100 % Polyester, with Blackout 3 pass Coating</p> <p>Thickness : 0.60 MM</p> <p>Openness Factor : 0%</p> <p>Weight : 390 GSM</p> <p>EPI / PPI - 176/164</p> <p>WARP &amp; WEFT - 80 DEN TWISTED SD &amp; 300 DEN ROTO</p> <p>warranty - 1 year</p>			
<p>4. Classic Roller – Blind Blackout</p> <p>Make - Vista</p> <p>Shade- Opaque Sand</p> <p>ROLLER TUBE: Made of anodized aluminium 38 mm Dia. Of high strength alloy With wall thickness of 1.2 mm with spline adoptable to accommodate clutch.</p> <p>CLUTCH MECHANISM: Moulded plastic having antifriction additive with Glass fibre reinforcement. Should have a minimum lifting capacity of 8 lbs</p> <p>OPERATING CHAIN: made of 4.5mm plastic beads molded on 2.2mm thick polyester chord. The pitch of the bead is 6mm. Chain adoptable to the clutch pitch for smooth lifting &amp; lowering of blind.</p> <p>LOCKING MEMBER: stop locks for limit setting adoptable to the chain.</p> <p>LOAD TUBE : 38 mm Extruded aluminium wall thickness :1.2 mm + / - 5%</p> <p>Bonding ( Fabric &gt; Tube ) : 15 mm wide double sided adhesive tape</p> <p>Bottom Bar: aluminium extruded rail with a groove for fixing the fabric and powder coated in white. The fabric is fitted to the tube using plastic insert for perfect fall of fabric to avoid warpage / floating. Installation to be insert type with end caps.</p>	200 Sq. Ft.		

Vista Serene Opaque series to be with 0% Openness Composition : 100 % Polyester, with Blackout 3 pass Coating Thickness : 0.60 MM Openness Factor : 0% Weight : 390 GSM EPI / PPI - 176/164 WARP & WEFT - 80 DEN TWISTED SD & 300 DEN ROTO warranty - 1 year			
5. Curtains Fabric: 260 GSM, Shade 419	23.5 Mts		
6. Curtains Fabric: 260 GSM, Shade 327A	307.5 Mts		
7. Curtain rod: S S, 18 Gauge, 1" Pipe	270 RFt.		
8. Side Fitting For Curtain rod: SS	27 Sets		
9. Centre Support For Curtain rod: SS	27 Pcs.		
<b>TOTAL</b>			
<b>GST</b>			
<b>TOTAL COST</b>			

Date:

Name of Agency:

Seal:

Signature: